



Acid-Chemical Hose

Mustang®
(Specification 4695, 4695G)

Black Cover (4695)

Nom. I.D.	⊖	Nom. O.D.	⊕	Max. W.P.	⊕	Suction		Min. Bend Radius	⊕	Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
3/4	19.1	1.25	31.8	200	1.38	30.0	762	4.0	102	.45	.20	100 ft.	X	4695-0002	
3/4	19.1	1.25	31.8	200	1.38	30.0	762	4.0	102	.45	.20	200 ft.	X	4695-0737	
1	25.4	1.50	38.1	200	1.38	30.0	762	5.0	127	.56	.25	100 ft.	X	4695-0003	
1	25.4	1.50	38.1	200	1.38	30.0	762	5.0	127	.56	.25	200 ft.	X	4695-0670	
1 1/4	31.8	1.75	44.5	200	1.38	30.0	762	6.0	152	.70	.32	100 ft.	X	4695-0004	
1 1/4	31.8	1.75	44.5	200	1.38	30.0	762	6.0	152	.70	.32	200 ft.	X	4695-0738	
1 1/2	38.1	2.04	51.8	200	1.38	30.0	762	8.0	203	.87	.40	100 ft.	X	4695-0005	
1 1/2	38.1	2.04	51.8	200	1.38	30.0	762	8.0	203	.87	.40	200 ft.	X	4695-0729	
2	50.8	2.54	64.5	200	1.38	30.0	762	9.0	229	1.08	.49	100 ft.	X	4695-0001	
2	50.8	2.54	64.5	200	1.38	30.0	762	9.0	229	1.08	.49	200 ft.	X	4695-0698	
2 1/2	63.5	3.05	77.5	150	1.03	30.0	762	12.0	305	1.41	.64	100 ft.	X	4695-0006	
2 1/2	63.5	3.05	77.5	150	1.03	30.0	762	12.0	305	1.41	.64	200 ft.	X	4695-0720	
3	76.2	3.58	90.9	150	1.03	30.0	762	18.0	457	1.81	.82	100 ft.	X	4695-0007	
3	76.2	3.58	90.9	150	1.03	30.0	762	18.0	457	1.81	.82	200 ft.	X	4695-0699	
4	101.6	4.69	119.1	125	.86	30.0	762	24.0	610	2.72	1.24	100 ft.	X	4695-0008	
4	101.6	4.69	119.1	125	.86	30.0	762	24.0	610	2.72	1.24	200 ft.	X	4695-0055	

Green Cover (4695G)

Nom. I.D.	⊖	Nom. O.D.	⊕	Max. W.P.	⊕	Suction		Min. Bend Radius	⊕	Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1	25.4	1.50	38.1	200	1.38	30.0	762	5.0	127	.56	.25	100 ft.	X	4695-0628	
1 1/2	38.1	2.04	51.8	200	1.38	30.0	762	8.0	203	.87	.40	100 ft.	X	4695-0211	
2	50.8	2.54	64.5	200	1.38	30.0	762	9.0	229	1.08	.49	100 ft.	X	4695-0216	
2	50.8	2.54	64.5	200	1.38	30.0	762	9.0	229	1.08	.49	200 ft.	X	4695-0700	
3	76.2	3.58	90.9	150	1.03	30.0	762	18.0	457	1.81	.82	100 ft.	X	4695-0229	
3	76.2	3.58	90.9	150	1.03	30.0	762	18.0	457	1.81	.82	200 ft.	X	4695-0701	

RECOMMENDED FOR: Tank truck, barge, ship, or storage tank transfer of a variety of chemical products. Mustang contains a wire helix for full suction capability, as well as for routing hoses through tight bends. Its Modified Cross-linked Polyethylene tube stock is "best in class" for maintaining a tight seal with stainless steel fittings, and is designed for cleaning with "open end" 50 PSI steam or in a bath containing 10% (NaOH) @ 212°F (100°C). Cleaning in place (CIP) methods may be used. Applications include over 950 basic chemicals that are building blocks for numerous chemicals used in a variety of industries. Reference Gates Chemical Resistance Table for proper hose selection.

CAUTION: For applications requiring greater than 90% sulfuric acid contact Denver Product Application (303) 744-5070.

Mustang is designed to withstand fluid temperatures to 250°F (+121°C), however the rating is dependent on the specific chemical conveyed. Contact Denver Product Application (303) 744-5070 for any chemical above 125°F (+52°C). NOT RECOMMENDED FOR "CLOSED STEAM" CLEANING.

TEMPERATURE: -40°F to +250°F (-40°C to +121°C) normal service.

CONSTRUCTION:
Tube: Type K (Gatrom™ Modified Cross-linked Polyethylene.) Tan. High chemical resistance.
Reinforcement: Synthetic, high tensile textile cord with steel wire helix.
Cover: Type P (EPDM). Black or green corrugated with orange spiral stripe. Blue, red, and yellow covers available on special order.

Design Factor: 4:1

COUPLINGS: Gates has tested hose assemblies at the maximum rated service temperature to assure your safety. Use 7, 8, or 49 for fluid temperatures to 125°F (+52°C). Use permanent fittings only 71 or 73 for fluid temperatures above 125°F (+52°C) and up to 250°F (+121°C) or 80 Gates GSP (2" only). Reference the Hose Coupling Section.

PACKAGING: All lengths coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: "GATES® Mustang® Acid-Chemical Suction/Discharge 200 PSI (1.38MPa) WP Made In U.S.A. For your safety: Use Permanent Couplings above 125°F."

SPECIAL ORDER REQUIREMENTS: Blue, red, and yellow covers are made to order and require minimum production order quantities of 400 feet per size. For price, add 10% (x1.10) to price.

Special production runs require minimum order quantities of 400 feet per size. If a special transfer label is required, contact Gates Corporation for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Gates Corporation for pricing, order requirements and availability.



Acid-Chemical Hose

77B (Paint Spray and Chemical)

(Specification 3207T)

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊖	Suction	⊖	Min. Bend Radius	⊖	Wt. Per Ft.	⊖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.52	13.2	500	3.45	30.0	762	3.0	76	.09	.04	Reel	X	3207-0290	
5/16	7.9	.59	15.0	500	3.45	30.0	762	3.0	76	.11	.05	Reel	X	3207-0291	
3/8	9.5	.67	17.0	500	3.45	30.0	762	3.0	76	.14	.06	Reel	X	3207-0292	
1/2	12.7	.87	22.1	750	5.17	25.0	635	5.0	127	.23	.10	Reel	X	3207-0294	
3/4	19.1	1.16	29.5	750	5.17	25.0	635	6.0	152	.35	.16	Reel	X	3207-0296	

RECOMMENDED FOR: Paint spray applications, as well as transfer of petroleum based products (aliphatic, aromatic and chlorinated hydrocarbon such as Toluene, Xylene, Benzene, gasoline and carbon tetrachloride). Reference Gates Chemical Resistance Table for proper hose selection. Compatible with commercially available Bio-Diesel fuels up to B-100.

CAUTION: Contact Denver Product Application (303) 744-5070 when conveying chemicals above 120°F (+49°C). NOT RECOMMENDED FOR ACIDS OR USE IN HIGH PRESSURE PAINT SPRAY APPLICATIONS REQUIRING A STATIC CONDUCTIVE HOSE.

TEMPERATURE: -40°F to +150°F (-40°C to +66°C) continuous service.

CONSTRUCTION:
Tube: Type Z (Special Flexible Nylon II). Clear.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type A (Neoprene). Black.
Design Factor: 4:1

COUPLINGS: 48. For paint service: Binks 3 piece compression ring only. Reference the Hose Coupling Section.

PACKAGING: 1/4" through 1/2": Packaged in 600' to 800' reels. Maximum 4 pieces. One length 25' to 50'. Maximum of 2 pieces under 100'.
 3/4": Packaged in 300' to 400' reels. Maximum 3 pieces. One length between 25' to 50'. All other lengths over 50'. Maximum 2 pieces under 100'.

BRANDING: Continuous ink print label. Example: "GATES® 77B PAINT SPRAY AND CHEMICAL 3/8" (9.5mm) 500 PSI (3.45MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet for all sizes.
REMNANT LENGTHS: None.



Air and Multi-Purpose Hose

19B Plant Master® (Specification 3219AR)

Nom. I.D.	⊖		⊕		Max. W.P.	○		Min. Bend Radius	⚖		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
	(In.)	(mm)	(In.)	(mm)		(psi)	(MPa)		(In. Hg)	(mm Hg)				
3/16	4.8	.43	10.9	315	3.45	30.0	762	3.0	76	.20	.09	Reel	5,000 ft.	3219-2901
1/4	6.4	.50	12.7	315	1.72	30.0	762	3.0	76	.09	.04	Reel	X	3219-2902
1/4	6.4	.62	15.8	500	3.45	30.0	762	3.0	76	.14	.06	Reel	5,000 ft.	3219-2903
5/16	7.9	.62	15.8	315	1.72	30.0	762	3.0	76	.13	.06	Reel	X	3219-2904
5/16	7.9	.69	17.5	500	3.45	30.0	762	3.0	76	.17	.08	Reel	5,000 ft.	3219-2905
3/8	9.5	.69	17.5	315	1.72	30.0	762	3.0	76	.15	.07	Reel	X	3219-2906
3/8	9.5	.75	19.1	500	3.45	30.0	762	3.0	76	.24	.11	Reel	5,000 ft.	3219-2907
1/2	12.7	.84	21.3	315	1.72	25.0	635	5.0	127	.20	.09	Reel	X	3219-2908
1/2	12.7	.88	22.4	500	3.45	25.0	635	5.0	127	.23	.10	Reel	5,000 ft.	3219-2909
5/8	15.9	.94	23.9	315	1.72	20.0	508	6.0	152	.24	.11	Reel	X	3219-2910
5/8	15.9	1.00	25.4	500	3.45	20.0	508	6.0	152	.27	.12	Reel	5,000 ft.	3219-2911
3/4	19.1	1.09	27.7	315	1.72	20.0	508	6.0	152	.29	.13	Reel	X	3219-2912
3/4	19.1	1.19	30.2	500	3.45	20.0	508	6.0	152	.38	.17	Reel	5,000 ft.	3219-2913
1	25.4	1.38	35.1	315	1.72	10.0	254	8.0	203	.41	.19	Reel	X	3219-2914
1	25.4	1.50	38.1	500	3.45	20.0	508	8.0	203	.55	.25	Reel	5,000 ft.	3219-2915

NOTE: 500 PSI is cancelled and available until stock depleted.

RECOMMENDED FOR: Applications requiring a premium grade braided hose, with excellent flexibility and maximum resistance to air, water, petroleum oils, gasoline, kerosene and fuel oil (to 120°F) and lubricating oils (to 212°F). Excellent weather and ozone resistance.

CAUTION: Not recommended for constant contact with fuels. Not recommended for Bio-Diesel fuels.

TEMPERATURE: -40°F to +212°F (-40°C to +100°C) continuous service.

CONSTRUCTION:
Tube: Type C (Nitrile). Black.
Reinforcement: Braided, high tensile synthetic textile cord.
Cover: Type C2 (Modified Nitrile). Red.
Design Factor: 4:1

COUPLINGS: 19 (up through 1/2" only), 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 1, 14, or 15 (all sizes), 72 Gates Power Crimp[®] or 75 Gates GLX[®]. Reference the Hose Coupling Section.

PACKAGING: 3/16" through 1/2": Packaged in 500' to 750' reels. Maximum 3 pieces. Minimum length 50'.
 5/8" through 1": Packaged in 400' to 650' reels. Maximum 3 pieces. Minimum length 50'.

BRANDING: Continuous ink brand. Example: "GATES® 19B Plant Master® Multi-Purpose 3/8" (9.5mm) 250 PSI (1.72MPa) WP Made in U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet.

REMNANT LENGTHS: None.

STANDARDS: Nonconductive at 1000 volts D.C. Electrical resistance is greater than one megohm per inch when subjected to 1000 volts D.C. Storage and use may adversely affect electrical properties.

Tube: ARPM (Class A) High oil resistance.
Cover: ARPM (Class B) Medium oil resistance.



Air and Multi-Purpose Hose

Terminator® (Specification 3202T, 3202TW)

Standard Reel Packaging

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊖	Suction	⊖	Min. Bend Radius	⊖	Wt. Per Ft.	⊖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.57	14.5	501	3.45	30.0	762	3.0	76	.15	.07	Reel	X	3202-0001	
3/8	9.5	.75	19.1	501	3.45	25.0	635	3.0	76	.19	.09	Reel	X	3202-0006	
1/2	12.7	.89	22.6	501	3.45	25.0	635	5.0	127	.25	.11	Reel	X	3202-0011	
3/4	19.1	1.22	31.0	501	3.45	15.0	381	6.0	152	.45	.20	Reel	X	3202-0016	
1	25.4	1.51	38.4	501	3.45	10.0	254	8.0	203	.57	.26	Reel	X	3202-0021	
1 1/4	31.8	1.78	45.2	501	3.45	10.0	254	10.0	254	.73	.33	Reel	X	3202-0027	
1 1/2	38.1	2.09	53.1	501	3.45	10.0	254	12.0	305	.96	.44	100 ft.	X	3202-0029	
2	50.8	2.64	67.1	501	3.45	10.0	254	14.0	356	1.35	.61	100 ft.	X	3202-0032	
2	50.8	2.64	67.1	501	3.45	10.0	254	14.0	356	1.35	.61	200 ft.	400 ft.	3202-0033	

Exact Length 500 Foot One Piece Reels

Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊖	Suction	⊖	Min. Bend Radius	⊖	Wt. Per Ft.	⊖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.57	14.5	501	3.45	30.0	762	3.0	76	.12	.05	Reel	500 ft.	3202-0301	
3/8	9.5	.75	19.1	501	3.45	25.0	635	3.0	76	.19	.09	Reel	500 ft.	3202-0306	
1/2	12.7	.89	22.6	501	3.45	25.0	635	5.0	127	.25	.11	Reel	500 ft.	3202-0311	
3/4	19.1	1.22	31.0	501	3.45	15.0	381	6.0	152	.42	.19	Reel	500 ft.	3202-0316	

RECOMMENDED FOR: Applications requiring a premium-quality, multi-purpose hose with superior abrasion resistance for air, oil and some chemical applications. Excellent durability for extra long life in these applications: mining, air drill, construction, poultry plants and other severe service. Good weather and ozone resistance.

CAUTION: Due to Terminator's 501 PSI working pressure, care should be taken to properly select couplings to match. Hose assembly working pressure is the working pressure of the lowest rated component.

TEMPERATURE: -40°F to +212°F (-40°C to +100°C) continuous service.

CONSTRUCTION:
Tube: Type C (Nitrile). Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type C4 (Carboxylated Nitrile). Yellow.
Design Factor: 4:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 15, 71, 72 Gates Power Crimp®, 73 (up to 250 psi), 74 Gates Mega Crimp®, 75 Gates GLX® or 80 Gates GSP (1 1/2" or 2" only). Reference the Hose Coupling Section.

PACKAGING: Exact length reels: 500' in one continuous length.
 Minimum of 90% of hose reels will be 1-piece lengths.
 1/4" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.
 1" and 1 1/4": Packaged in 300' to 400' reels. Maximum 3 pieces. Minimum length 50'.
 1 1/2" and 2": Packaged 100' coiled and wrapped in polyethylene.

BRANDING: Continuous ink brand. Example: "GATES® TERMINATOR® 501 PSI (3.45MPa) WP 3/4" (19.1mm) FLAME RESISTANT MSHA 2G-IC-11C MADE IN USA"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet for sizes through 3/4", 5,000 feet for 1" and 1 1/4", 400 feet for 1 1/2" and larger.
 Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: None.

STANDARDS: Meets MSHA 30 CFR 18.65. Flame resistant. All sizes except 1 1/2" and 2" are nonconductive at 1000 volts D.C. Electrical resistance is greater than one megohm per inch when subjected to 1000 volts D.C. Storage and use may adversely affect electrical properties.

Tube: ARPM (Class A) High oil resistance.
Cover: ARPM (Class A) High oil resistance.



Air and Multi-Purpose Hose

LOL (Lock-On Hose)

(Specification 3284D, E, G, H, R, Y)

Color	Nom. I.D.	⊖	Nom. O.D.	⊖	Max. W.P.	⊖	Suction		Min. Bend Radius	⊖	Wt. Per Ft.	⊖	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
	(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
Black	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	Reel	X	3201-1100	
Black	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	Reel	X	3201-1101	
Black	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	Reel	X	3201-1102	
Black	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	Reel	X	3201-1103	
Black	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	Reel	X	3201-1104	
Blue	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	Reel	X	3201-1105	
Blue	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	Reel	X	3201-1106	
Blue	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	Reel	X	3201-1107	
Blue	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	Reel	X	3201-1108	
Blue	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	Reel	X	3201-1109	
Red	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	Reel	X	3201-1110	
Red	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	Reel	X	3201-1111	
Red	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	Reel	X	3201-1112	
Red	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	Reel	X	3201-1113	
Red	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	Reel	X	3201-1114	
Green	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	Reel	X	3201-1120	
Green	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	Reel	X	3201-1121	
Green	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	Reel	X	3201-1122	
Green	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	Reel	X	3201-1123	
Green	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	Reel	X	3201-1124	
Gray	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	Reel	X	3201-1125	
Gray	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	Reel	X	3201-1126	
Gray	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	Reel	X	3201-1127	
Gray	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	Reel	X	3201-1128	
Gray	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	Reel	X	3201-1129	
Yellow	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	Reel	X	3201-1115	
Yellow	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	Reel	X	3201-1116	
Yellow	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	Reel	X	3201-1117	
Yellow	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	Reel	X	3201-1118	
Yellow	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	Reel	X	3201-1119	

RECOMMENDED FOR: Petroleum-base hydraulic oils, water, glycol antifreeze solutions, hot lubricating oils, and air.

CAUTION: Lock-On hose and couplings are not recommended for pressure surge applications or critical applications, such as permanent piping in residential or commercial buildings. Not recommended for gasoline or diesel fuels.

TEMPERATURE: -40°F to +212°F (-40°C to +100°C) normal service. For air: 160°F (+71°C) only. For water emulsion, see Gates Hydraulic Hose Catalog #35093.

CONSTRUCTION: **Tube:** Type C (Nitrile), Black.
Reinforcement: Braided, high tensile synthetic textile cord.
Cover: Type C2 (Modified Nitrile).
Design Factor: 4:1

COUPLINGS: 75 Gates GLX®, Gates Hydraulic Lock-On Couplings. NOTE: Do not use clamps with Lock On fittings. (Reference Gates Hydraulic Hose Catalog #35093) or clamp over beaded nipple. Reference the Hose Coupling Section.

PACKAGING: 1/4" through 1/2": Packaged in 300' reels. Maximum of 3 pieces per reel. Minimum length 50'.
 5/8": Packaged in 250' reels. Maximum of 3 pieces per reel. Minimum length 50'.
 3/4": Packaged in 225' reels. Maximum of 3 pieces per reel. Minimum length 50'.

BRANDING: Continuous ink brand. Example: "GATES® LOL 12LOLA 3/4 INCH 300 PSI WP FLAME RESISTANT COVER MADE IN U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: Black cover meets MSHA 30 CFR 18.65. Flame resistant.
Tube: ARPM (Class A) High oil resistance.
Cover: ARPM (Class B) Medium oil resistance. Flame resistant.