All of the SUNFLEX ® 8 basic parts:

Available in size: $\frac{1}{2}$ ", $\frac{3}{4}$ ", $\frac{1}{3}$ ", $\frac{1}{4}$ ", $\frac{1}{4}$ ", $\frac{1}{4}$ ", $\frac{2}{3}$ ", $\frac{2}{4}$ ", $\frac{2}{3}$ ", $\frac{4}{4}$ ", $\frac{5}{6}$ ", $\frac{6}{3}$ "

Material of Body: Brass Aluminum

Stainless Steel (By Investment Cast)

CAM & GROOVE COUPLINGS FOR HOSE & PIPE





Buna N: Buna N is standard. It is generally recommended for petroleum derivates, neutral or slightly acidic salt solutions, alcohols, ethers, glycols, fats, oils, and greases. This compound should give good service from -40°F to +250°F.

Neoprene: Recommended for alkaline and acid salt solutions and aldehydes such as formaldehyde. For food service. White neoprene is also available. Temperature recommended -40°F to +250°F.

TWO LUG UNIVERSIAL CROWFOOT HOSE COUPLINGS (FOR AIR HOSE) TWO SEALS IN ONE MAKE COUPLING AN EASY TASK



MALE THREAD END Size From 1/4" - 2"



HOSE END Size From 1/4 * - 2*



FEMALE THREAD END Size From 1/4* - 2 *



THREE - WAY CONNECTION



MALE PIPE(N.P.T.)STEM



HOSE STEM WITH WING NUT & FEMALE SPUD Size From 1/2" - 4"



HOSE MENDERS Steel, Plated Size From 1/2 - 8



COMBINATION HOSE SHANK NIPPLES Steel, Plated Or Plain Size From 1/2" - 10 "



SUCTION HOSE COUPLING Brass Hose Shank, Aluminum Hose Shank With Brass Pin Lug Swivel Size From 1/2" - 6"



HOSE COUPLINGS (FOR SANDBLAST HOSE) Brass, Aluminum Size From 3/4" - 2"



DOUBLE BOLT CLAMP Size From 1/2" - 12"



10-10

HOSE CLAMP WITH SAFETY CLAW Size From 1/2" - 4"